Specification Sheet SS-35-450-0310 March 2010

The NEWAGE® 35-450 Series Brinell Scope features a calibrated reticle in a flat field optical system. This economical instrument accurately measures the indentation diameter from any Brinell hardness tester.

The model 35-450 is a compact, portable reader with a fixed 20X focus. Its illumination system uses an incandescent flashlight for lillumination. The flashlight is powered with a single AAA battery, included with the instrument. The reticle is calibrated in 0.1mm units over a range of 6mm. The field of vision is 7mm.

### **Features**

- Flashlight source is economical
- Battery operated- uses a single AAA battery (included)
- Use on any Brinell applications
- 6mm Reticle scale, 0.1mm scale divisions, 7mm field diameter
- 20X magnification, fixed focus
- Easy-to-Use
- Compact size

### **Specifications**

Magnification:20XReticule Scale:6mmScale Divisions:0.1mmField Diameter:7mmPower:AAA Batt

Power: AAA Battery)
Instrument Weight: 1.5 lbs (700 g)
Shipping Weight: 2 lbs (1 kg)







# **Ordering**

#### Model 35-450 Series Pocket Brinell Scope

Model	Description
35-450	Pocket Scope, 20X, fixed focus with case

## Reference

Indenter	Hardness Number		l	Indenter	Hardness Number	
Diameter	for Applied Load			Diameter	for Applied Load	
mm	500	3000		mm	500	3000
2.0	157.5	945.3		4.5	29.8	178.5
2.1	142.7	856.5		4.6	28.4	170.4
2.2	129.9	779.5		4.7	27.1	162.8
2.3	118.7	712.4		4.8	25.9	155.6
2.4	108.9	653.4		4.9	24.8	148.9
2.5	100.2	601.5		5.0	23.8	142.6
2.6	92.6	555.3		5.1	22.8	136.6
2.7	85.7	514.2		5.2	21.8	131.0
2.8	79.6	477.5		5.3	20.9	125.6
2.9	74.1	444.4		5.4	20.1	120.6
3.0	69.1	414.6		5.5	19.3	115.9
3.1	64.6	387.7		5.6	18.6	111.4
3.2	60.5	363.2		5.7	17.8	107.1
3.3	56.8	340.9		5.8	17.2	103.0
3.4	53.4	320.6		5.9	16.5	99.2
3.5	50.3	302.0		6.0	15.9	95.5
3.6	47.5	284.8		6.1	15.3	92.0
3.7	44.9	269.1		6.2	14.8	88.7
3.8	42.4	254.6		6.3	14.2	85.5
3.9	40.2	241.2		6.4	13.7	82.5
4.0	38.1	228.8		6.5	13.3	79.6
4.1	36.2	217.2		6.6	12.8	76.8
4.2	34.4	206.5		6.7	12.4	74.1
4.3	32.8	196.5		6.8	11.9	71.6
4.4	31.2	187.2		6.9	11.5	69.1



## **MEASUREMENT & CALIBRATION TECHNOLOGIES**

For the authorized Newage Distributor or Manufacturer's Representative near you, go to www.hardnesstesters.com

Newage Testing Instruments, Inc. An AMETEK Company 820 Pennsylvania Blvd. Feasterville, PA 19053 United States of America
Tel +1-215-355-6900 (Sales)
Tel +1-800-806-3924 (Sales)

+1-800-317-1976 (Service)

Fax +1-215-526-2192 Email newage.info@ametek.com



Ph: (02) 9545 4433

Fax: (02) 9545 4218

