

EchoMix®

Powder Ultrasonic Couplant

EchoMix is easily mixed in ambient water in five minutes, providing a gel with a strong, continuous coupling film that adheres well to vertical and overhead surfaces.

PRODUCT DESCRIPTION

Most economical ultrasonic couplant available.

Salt stable – will not thin with corrosion salts or in marine or highway environments.

Fast, easy removal with water.

Low toxicity and low environmental impact.

Compact for shipping and storing.

Easy mixing, fast gel time in ambient water (5 minutes to final product).

EchoMix 2-Part Powder

Strongest coupling film of powder couplants
Blue mixing tracer
2-part (two packets)

EchoMix Single 1-Part Powder

Easiest mixing powder couplant
One packet
Less residue
Blue mixing tracer



PRODUCT SPECIFICATIONS

Operating Range: 32° to 120°F (0° to 50°C)

- **Viscosity:** 23,000 CPS, Brookfield #4 Spindle, 6 rpm
- **pH:** 9
- **Corrosion Inhibition:** Contains mild short term Ferrous Corrosion Inhibitors
- **Compliance:**
ASME Boiler & Pressure Vessel Code (T-533)
NAVSHIPS 250-1500
FAA-AC #25-29 (Glycerin-free)
Less than 0.02% (200 ppm) Halogens & Sulfur

PACKAGING

1 and 5 gallon easy to open and easy to use powder packets.

SDS available at www.echoultrasonics.com

ECHO
ultrasonics



Russell Fraser Sales Pty Ltd

Unit 7/38 Waratah St
Kirrawee NSW 2232

Ph: (02) 9545 4433

Email: rfs@rfsales.com.au

Web: www.rfsales.com.au

ABN: 79 074 258 549