



CircleSafe® 778A

Physical Characteristics

Forest green solution with a slight detergent odor, contained in an aerosol package.

Particle Certification

Particles meet or exceed all relevant specifications including but not limited to ASTM E 1444, MIL-STD-271, NAVSEA 250-1500-1, ASTM E 709 and ASME B & PV Code - Section V and AMS 3044. Certification is included with each shipment.

Particle Color

Fluorescent Yellow-Green

Average Particle Size

5 µm

AMS Standard

3044

SAE Sensitivity*

8

[*Representative of the number of lines shown on a tool steel ring as defined in SAE AS5282.]

Temperature Limit

120°F Maximum

Related Product Information:

Safety Data Sheet
Technical Bulletin 268

Item

FG-3590

Package Size

Case of 12 x 16 oz. Cans

CircleSafe® 778A is an aerosol spray can of Mi-Glow® 800 fluorescent yellow-green particles and liquid Wetting Agent 771, formulated in water media. It is designed to be used with UV-A light inspection to detect very fine discontinuities found in finished products and critical, highly stressed component parts.

Its ultra-bright, ultra-sensitive particles allow for excellent detection. This aerosol is packaged in a carbon dioxide propellant for odor-free, fume-free, non-combustible inspection.



Russell Fraser Sales Pty Ltd

Unit 10 / 1-11 Burns Road, Heathcote NSW 2233 Australia

Ph: +61 2 9545 4433 Email: rfs@rfsales.com.au Website: rfsales.com.au