




ASTM E3022-18 Standard MEETS EN ISO:3059 Specifications

INTRODUCING THE

HIGHEST QUALITY LONGEST RUNNING MOST CONVENIENT

COMPLIANT LED UV-A FLASHLIGHT IN THE WORLD!





WHY CLARITY™?



LONGEST BATTERY LIFE ON THE MARKET



AUTO SHUT-OFF
Keeps Intensity Above
Minimum Output





THE SPECTROLINE® DIFFERENCE

Spectroline has over 60 years of experience working alongside NDT inspectors, engineers, and organization members to design, test, and deliver UV-A inspection lamps of the highest quality.



MODEL	NOMINAL STEADY-STATE UV-A (365 nm) INTENSITY at 15 in (38 cm) •	VISIBLE LIGHT MEASUREMENT	UV-A COVERAGE DIAMETER at 15 in (38 cm) at minimum 1,000 μW/cm²
SPN-CLR365-HC	6,750 μW/cm²	< 1 foot-candle (11 lux)	3 in (7.62 cm)
SPN-CLR365-SC	4,500 μW/cm²	< 1 foot-candle (11 lux)	4 in (10.1 cm)

CLARITY 365

Light Source: (1) UV-A LED Lamp Style: Cordless Flashlight **Lamp Head Diameter:** 1 in (2.7 cm) Length: 7 in (17.8 cm) Weight: 0.8 lbs (363 g) (with Battery) **Power Requirements:** Lithium-Ion Battery **Run Time:** 9 hours (continuous) **Charge Time:** 6 Hours

 Φ UV-A intensity reading taken with the Spectroline® AccuMAXTM Series meter, and is factory set to the value shown.

CLARITY™ 365 KIT

Kit Includes:

Flashlight with battery, induction charging dock, AC power cord, USB power cord, belt holster, UV-absorbing spectacles, comes in carrying case.

UV-A Beam Profile

Surface Contour Profile at 15 in (38 cm) Top Intensity Profile at 15 in (38 cm) **SPN-CLR365-HC MODEL** UV-A INTENSITY INTENSITY MODEL 10000 5000 CERTIFICATE OF CONFORMANCE 1000 200 -2 -1 (-5.1) (-2.5) (0) (2.5) SPN-CLR365-SC MODEL UV-A INTENSITY 5000 $C \in$ (0) 1000 200 4 -3 -2 -1 0 1 2 3 (-10) (-7.6) (-5.1) (-2.5) (0) (2.5) (5.1) (7.6) **STANDARD**



Russell Fraser Sales Pty Ltd

X-INCHES (cm)

Unit 7/38 Waratah St Kirrawee NSW 2232 Ph: (02) 9545 4433 Email: rfs@rfsales.com.au

ABN: 79 074 258 549

Web: www.rfsales.com.au

INTENSITY MODEL