

DUBL-CHEK DR-60 Aerosol

Callington Haven Pty Ltd

Chemwatch: 5147-53 Version No: 6.1.1.1 Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **28/05/2019**Print Date: **29/05/2019**S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	DUBL-CHEK DR-60 Aerosol
Synonyms	Not Available
Proper shipping name	AEROSOLS
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Application is by spray atomisation from a hand held aerosol pack Used in NDT testing as cleaner/remover.

Details of the supplier of the safety data sheet

Registered company name	Callington Haven Pty Ltd
Address	30 South Street Rydalmere NSW 2116 Australia
Telephone	+61 2 9898 2700
Fax	+61 2 9475 0449
Website	www.callingtonhaven.com
Email	customerservice@callington.com

Emergency telephone number

Association / Organisation	Chemwatch	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	Not Available	+61 1800 951 288
Other emergency telephone numbers	Not Available	+61 2 9186 1132

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification [1]	Aerosols Category 1, Specific target organ toxicity - single exposure Category 3 (narcotic effects)	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)





SIGNAL WORD	DANGER

Hazard statement(s)

nazaru statement(s)	
H222	Extremely flammable aerosol.
H336	May cause drowsiness or dizziness.
AUH044	Risk of explosion if heated under confinement.

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Pressurized container: Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing mist/vapours/spray.

Chemwatch: 5147-53 Page 2 of 9 Issue Date: 28/05/2019 Version No: 6.1.1.1 Print Date: 29/05/2019

DUBL-CHEK DR-60 Aerosol

Precautionary statement(s) Response

P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

Precautionary statement(s) Storage

P405	05 Store locked up.	
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.	
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	

Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
64742-48-9.	>60	naphtha petroleum, heavy, hydrotreated
68476-85-7.	20-40	hydrocarbon propellant

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If furnes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor.
Ingestion	Not considered a normal route of entry. If swallowed do NOT induce vomiting. If towniting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink. Seek medical advice.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to petroleum distillates or related hydrocarbons:

- Primary threat to life, from pure petroleum distillate ingestion and/or inhalation, is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (e.g. cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial injury has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Figure phrine (adrenalin) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination, ensure use of cuffed endotracheal tube in adult patients. [Ellenhorm and Barceloux: Medical Toxicology]

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with strong oxidising agents as ignition may result

Chemwatch: 5147-53 Page 3 of 9 Issue Date: 28/05/2019 Version No: 6.1.1.1 Print Date: 29/05/2019

DUBL-CHEK DR-60 Aerosol

Advice for firefighters Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course. If safe, switch off electrical equipment until vapour fire hazard removed. Fire Fighting Use water delivered as a fine spray to control fire and cool adjacent area DO NOT approach containers suspected to be hot. Cool fire exposed containers with water spray from a protected location. If safe to do so, remove containers from path of fire. ► Equipment should be thoroughly decontaminated after use. ▶ Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat or flame. Vapour forms an explosive mixture with air. Severe explosion hazard, in the form of vapour, when exposed to flame or spark Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition with violent container rupture. Aerosol cans may explode on exposure to naked flames Fire/Explosion Hazard Rupturing containers may rocket and scatter burning materials. Hazards may not be restricted to pressure effects. May emit acrid, poisonous or corrosive fumes On combustion, may emit toxic fumes of carbon monoxide (CO). Other combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material.

SECTION 6 ACCIDENTAL RELEASE MEASURES

HAZCHEM

Personal precautions, protective equipment and emergency procedures

Not Applicable

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Wear protective clothing, impervious gloves and safety glasses. Shut off all possible sources of ignition and increase ventilation. Wipe up. If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water courses No smoking, naked lights or ignition sources. Increase ventilation. Stop leak if safe to do so. Water spray or fog may be used to disperse / absorb vapour. Absorb or cover spill with sand, earth, inert materials or vermiculite. If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Collect residues and seal in labelled drums for disposal.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

- ▶ Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT enter confined spaces until atmosphere has been checked Avoid smoking, naked lights or ignition sources. Avoid contact with incompatible materials. When handling, DO NOT eat, drink or smoke. Safe handling DO NOT incinerate or puncture aerosol cans DO NOT spray directly on humans, exposed food or food utensils. Avoid physical damage to containers.
 - Always wash hands with soap and water after handling.
 - Work clothes should be laundered separately.
 - Use good occupational work practice.
 - Observe manufacturer's storage and handling recommendations contained within this SDS.

Chemwatch: 5147-53 Page 4 of 9

Version No: 6.1.1.1 DUBL-CHEK DR-60 Aerosol

Issue Date: **28/05/2019**Print Date: **29/05/2019**

▶ Store in original containers in approved flame-proof area.

- ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- ▶ No smoking, naked lights, heat or ignition sources.
- ▶ Keep containers securely sealed. Contents under pressure.
- Store away from incompatible materials.
- ▶ Store in a cool, dry, well ventilated area in an upright position.
- ▶ Avoid storage at temperatures higher than 40 deg C.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

Suitable container

Other information

- ▶ Aerosol dispenser.
- ► Check that containers are clearly labelled.

Storage incompatibility

Avoid storage with oxidisers

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	naphtha petroleum, heavy, hydrotreated	Oil mist, refined mineral	5 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	hydrocarbon propellant	LPG (liquified petroleum	1000 ppm / 1800 ma/m3	Not Available	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
naphtha petroleum, heavy, hydrotreated	Naphtha, hydrotreated heavy; (Isopar L-rev 2)	350 mg/m3	1,800 mg/m3	40,000 mg/m3
hydrocarbon propellant	Liquified petroleum gas; (L.P.G.)	65,000 ppm	2.30E+05 ppm	4.00E+05 ppm

Ingredient	Original IDLH	Revised IDLH
naphtha petroleum, heavy, hydrotreated	2,500 mg/m3	Not Available
hydrocarbon propellant	2,000 ppm	Not Available

Exposure controls

Appropriate enginee	ring
cont	rols

Use in a well-ventilated area

General exhaust is adequate under normal operating conditions.

Personal protection









Eye and face protection

No special equipment for minor exposure i.e. when handling small quantities.

OTHERWISE: For potentially moderate or heavy exposures:

- Safety glasses with side shields.
- NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.

Skin protection

See Hand protection below

Hands/feet protection

- ▶ No special equipment needed when handling small quantities.
- OTHERWISE:
- For potentially moderate exposures:
 - Wear general protective gloves, eg. light weight rubber gloves.
 - ► For potentially heavy exposures:
 - Wear chemical protective gloves, eg. PVC. and safety footwear.

Body protection

No enocial equip

OIH

No special equipment needed when handling small quantities. **OTHERWISE:**

Other protection

- Overalls.
- Skin cleansing cream.

See Other protection below

- ► Eyewash unit.
- ▶ Do not spray on hot surfaces.

Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS P3	-	AX-PAPR-AUS / Class 1 P3
up to 50 x ES	-	AX-AUS / Class 1 P3	-

Issue Date: **28/05/2019**Print Date: **29/05/2019**

DUBL-CHEK DR-60 Aerosol

	1		
up to 100 x ES	-	AX-2 P3	AX-PAPR-2 P3 ^

^{^ -} Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Supplied as an aerosol pack. Contents under PRESSURE. Contains highly flammable hydrocarbon propellant. IClear highly flammable liquid with petroleum odour; dispersible in water.			
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not available.
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not available.	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	-84 propellant	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	9.5	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.8	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	345 @ 21C	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	>1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Elevated temperatures. Presence of open flame. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

illiorillation on toxicological	enecis		
Inhaled	Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. WARNING:Intentional misuse by concentrating/inhaling contents may be lethal.		
Ingestion	Not normally a hazard due to physical form of product. Ingestion may result in nausea, pain, vomiting. Vomit entering the lungs by aspiration may cause potentially lethal chemical pneumonitis.		
Skin Contact	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. The material may accentuate any pre-existing skin condition		
Eye	The material may be irritating to the eye, with prolonged contact causing inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.		
Chronic	Chronic solvent inhalation exposures may result in nervous system impairment and liver and blood changes. [PATTYS] Prolonged or continuous skin contact with the liquid may cause defatting with drying, cracking, irritation and dermatitis following. WARNING: Aerosol containers may present pressure related hazards.		
DUDI OUEK DD CO Assess	TOXICITY	IRRITATION	
DUBL-CHEK DR-60 Aerosol	Not Available	Not Available	
	TOXICITY	IRRITATION	
naphtha petroleum, heavy,	Dermal (rabbit) LD50: >1900 mg/kg ^[1]	Eye: no adverse effect observed (not irritating) ^[1]	
hydrotreated	Inhalation (rat) LC50: 8.5 mg/l/4H ^[2]	Skin: adverse effect observed (irritating) ^[1]	

Chemwatch: 5147-53 Page 6 of 9 Version No: 6.1.1.1

DUBL-CHEK DR-60 Aerosol

Issue Date: 28/05/2019 Print Date: 29/05/2019

	Oral (rat) LD50: >4500 mg/kg ^[1]			
hydrocarbon propellant	TOXICITY Not Available	IRRITATION Not Available		
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances			
NAPHTHA PETROLEUM, HEAVY, HYDROTREATED	oil, n-paraffins may be absorbed to a greater extent thar The major classes of hydrocarbons are well absorbed ir ingested in association with fats in the diet. Some hydroc hydrocarbons partly separate from fats and undergo me hydrocarbon that becomes available to be deposited undergo provided to the nervolument of the product contains benzene, which cat toxic to the nervous system. This product contains tolue contains ethyl benzene and naphthalene, from which ani Cancer-causing potential: Animal testing shows inhaling in humans. Mutation-causing potential: Most studies involving gasc studies in living human subjects (such as in petrol servi Reproductive toxicity: Animal studies show that high cor developmental toxicity to the nervous system of the foetu	tle absorption above C30. With respect to iso- or cyclo-paraffins. to the gastrointestinal tract in various sparbons may appear unchanged as in the tabolism in the gut cell. The gut cell may changed in peripheral tissues such as in a cause acute myeloid leukaemia, and nine, and animal studies suggest high coin mal testing shows evidence of tumour for petroleum causes tumours of the liver a soline have returned negative results regardes station attendants). In a centrations of toluene (>0.1%) can causes. Other studies show no adverse effects are defatting of the skin which can lead to	to the carbon chain lengths likely to be present in mineral species. In many cases, the hydrophobic hydrocarbons are not lipoprotein particles in the gut lymph, but most by play a major role in determining the proportion of the body fat stores or the liver. -hexane, which can be metabolized to compounds which are necentrations of toluene lead to hearing loss. This product immation. and kidney; these are however not considered to be relevant arding the potential to cause mutations, including all recent see developmental effects such as lower birth weight and so in the foetus.	
HYDROCARBON PROPELLANT				
Acute Toxicity	×	Carcinogenicity	×	
Skin Irritation/Corrosion	×	Reproductivity	×	
Serious Eye Damage/Irritation	×	STOT - Single Exposure	✓	
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×	
Mutagenicity	×	Aspiration Hazard	×	

Leaend:

X - Data either not available or does not fill the criteria for classification

Data available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DUBL-CHEK DR-60 Aerosol	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
naphtha petroleum, heavy,	LC50	96	Fish	4.1mg/L	2
hydrotreated	EC50	48	Crustacea	4.5mg/L	2
	EC50	72	Algae or other aquatic plants	>1-mg/L	2
	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	LC50	96	Fish	24.11mg/L	2
hydrocarbon propellant	EC50	96	Algae or other aquatic plants	7.71mg/L	2
	LC50	96	Fish	24.11mg/L	2
	EC50	96	Algae or other aquatic plants	7.71mg/L	2

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
	No Data available for all ingredients	No Data available for all ingredients

Bioaccumulative potential

Ingredient	Bioaccumulation

DUBL-CHEK DR-60 Aerosol

Issue Date: **28/05/2019**Print Date: **29/05/2019**

No Data available for all ingredients

Mobility in soil

Ingredient	Mobility
	No Data available for all ingredients

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Consult State Land Waste Management Authority for disposal.
- ▶ Discharge contents of damaged aerosol cans at an approved site.
- ► Allow small quantities to evaporate.
- ▶ DO NOT incinerate or puncture aerosol cans.
- ▶ Bury residues and emptied aerosol cans at an approved site.

SECTION 14 TRANSPORT INFORMATION

Labels Required



Marine Pollutant

NO Not Applicable

HAZCHEM

Not Applicable

Land transport (ADG)

UN number	1950		
UN proper shipping name	AEROSOLS		
Transport hazard class(es)	Class 2.1 Subrisk Not Applicable		
Packing group	Not Applicable		
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions 63 190 277 327 344 381		

Air transport (ICAO-IATA / DGR)

UN number	1950			
UN proper shipping name	Aerosols, flammable			
Transport hazard class(es)	ICAO/IATA Class 2.1 ICAO / IATA Subrisk Not Applicable ERG Code 10L			
Packing group	Not Applicable			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions Cargo Only Packing Instructions Cargo Only Maximum Qty / Pack Passenger and Cargo Packing Instructions Passenger and Cargo Maximum Qty / Pack Passenger and Cargo Limited Quantity Packing Instructions Passenger and Cargo Limited Maximum Qty / Pack		A145 A167 A802 203 150 kg 203 75 kg Y203 30 kg G	

Sea transport (IMDG-Code / GGVSee)

UN number	1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	IMDG Class 2.1 IMDG Subrisk Not Applicable

Issue Date: **28/05/2019**Print Date: **29/05/2019**

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

NAPHTHA PETROLEUM, HEAVY, HYDROTREATED(64742-48-9.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List
Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes
Australia Exposure Standards
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

IMO Provisional Categorization of Liquid Substances - List 2: Pollutant only mixtures containing at least 99% by weight of components already assessed by IMO

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Air Transport Association (IATA) Dangerous Goods Regulations

International FOSFA List of Banned Immediate Previous Cargoes
International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

(English)

HYDROCARBON PROPELLANT(68476-85-7.) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Dangerous Goods Code (ADG Code) - Dangerous Goods List

Australia Dangerous Goods Code (ADG Code) - List of Emergency Action Codes

Australia Dangerous Goods Code (ADG Code) - Packing Instruction - Liquefied and Dissolved Gases

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)

 $\label{eq:australia} \textbf{Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule}$

International Air Transport Association (IATA) Dangerous Goods Regulations International Maritime Dangerous Goods Requirements (IMDG Code)

United Nations Recommendations on the Transport of Dangerous Goods Model Regulations

ECHA SUMMARY

Ingredient	CAS number	Index No	ECHA Dossier
naphtha petroleum, heavy, hydrotreated	64742-48-9.	649-327-00-6	01-2119486659-16-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Asp. Tox. 1; Muta. 1B; Carc. 1B	GHS08; Dgr	H304; H340; H350
1	Flam. Liq. 3; Asp. Tox. 1; STOT SE 3	GHS02; GHS08; Dgr	H226; H304; H336

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

Ingredient	CAS number	Index No	ECHA Dossier
hydrocarbon propellant	68476-85-7.	649-202-00-6 649-203-00-1	01-2119485911-31-XXXXI01-2119490743-31-XXXX

Harmonisation (C&L Inventory)	Hazard Class and Category Code(s)	Pictograms Signal Word Code(s)	Hazard Statement Code(s)
1	Press. Gas; Flam. Gas 1; Muta. 1B; Carc. 1A	GHS02; GHS08; GHS04; Dgr	H220; H280; H340; H350
1	Flam. Gas 1; Muta. 1B; Carc. 1B	GHS02; GHS08; GHS04; Dgr	H220; H340; H350

Harmonisation Code 1 = The most prevalent classification. Harmonisation Code 2 = The most severe classification.

National Inventory Status

National Inventory	Status
Australia - AICS	Yes
Canada - DSL	Yes
Canada - NDSL	No (hydrocarbon propellant; naphtha petroleum, heavy, hydrotreated)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (naphtha petroleum, heavy, hydrotreated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Thailand - TECI	No (hydrocarbon propellant)
Legend:	Yes = All declared ingredients are on the inventory No = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

Chemwatch: 5147-53 Page 9 of 9 Issue Date: 28/05/2019 Version No: 6.1.1.1 Print Date: 29/05/2019

DUBL-CHEK DR-60 Aerosol

Revision Date	28/05/2019
Initial Date	24/07/2014

SDS Version Summary

Version	Issue Date	Sections Updated
2.1.1.1	24/07/2014	Engineering Control, Personal Protection (eye), Personal Protection (hands/feet)
6.1.1.1	28/05/2019	Acute Health (skin), Classification, Environmental, Fire Fighter (fire/explosion hazard), First Aid (eye), Ingredients, Physical Properties

Other information

Ingredients with multiple cas numbers

Name	CAS No
naphtha petroleum, heavy, hydrotreated	64742-48-9., 101795-02-2.
hydrocarbon propellant	68476-85-7., 68476-86-8.

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.